





# FORK-OIL 15W

Telescopic fork lubricant

#### SPECIFICS

- WP
- KAYABA
- SHOWA
- OHLINS
- HYPERSPORT
- SPORT-TOURER
- OFF-ROAD

## **TECHNICAL DESCRIPTION**

Hydraulic Fork Lubricant for Racing Applications is a specially formulated product designed for optimal performance in racing applications. It is manufactured through exclusive processes to ensure top performance, and is a fully synthetic solution that provides superior protection for mechanical parts, enhanced performance, and improved efficiency.

This product is recommended for use with all types of conventional telescopic forks or invertedstem forks on competition and motocross bikes, in accordance with the 15W viscosity grades outlined in the manufacturers' user and maintenance manuals.

The product offers the following key benefits:

- Ensures smooth suspension action.
- Anti-foaming properties.
- Maximum heat dissipation.
- Exceptional oxidation stability.
- Low pour point.
- Exceptionally high viscosity index.
- Low friction.
- Maximum compatibility with rubber parts.

For further details, please contact the technical department.



Via Boscofangone, Zona industriale ASI 80035 – NOLA (NA) – ITALIA Tel: 081 3151396/97 Fax: 081 3151605 Web: www.siralspa.it laboratorio@siralspa.it





# 1 L 4 L 5 L 208 L





19/11/2021 Rev. N°4 del 01/07/2024

## **TECHNICAL DATA SHEET**

# FORK-OIL 15W

## **Typical characteristics**

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	Kg/dm³	ASTMD7042	0,857
Viscosity 40°C	cSt	ASTMD445	47,37
Viscosity 100°C	cSt	ASTMD445	8,22
Viscosity Index	-	ASTMD2270	148,5
Flash Point	°C	ASTMD92	218
Freezing point	°C	ASTMD97	-43

#### **MODE OF USE**

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

#### **SAFETY AND ENVIRONMENT**

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



Via Boscofangone, Zona industriale ASI 80035 – NOLA (NA) – ITALIA Tel: 081 3151396/97 Fax: 081 3151605 Web: www.siralspa.it laboratorio@siralspa.it

Responsabile di laboratorio