



REDOIL



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY

Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

TECHNICAL DATA SHEET

COMPETITION GT4 5W-50

Four Stroke Motorcycle Lubricant

SPECIFICS

- API SP/ SN/SM
- JASO T903 JASO MA-MA2
- JASO Quality Category SP



TECHNICAL DESCRIPTION

Synthetic-Based Lubricant Fluid for 4-Stroke Engines is a synthetic-based modified lubricant fluid, produced through exclusive manufacturing processes with the objective of achieving maximum performance. This technological innovation represents the optimal combination of mechanical part protection, performance, and fuel consumption reduction.

This product has been specifically designed for all types of 4-stroke street motorcycle engines, with or without wet clutches. It is also suitable for use in jet skis, snowmobiles, SXS, and ATVs, in accordance with the viscosity grades specified in the manufacturers' user and maintenance manuals.

The product offers the following key benefits:

- An anti-hop function to provide superior clutch control.
- Exceptional protection for the catalytic converter (low phosphorus and sulfur content, JASO MA-2 compliant).
- Improved gear shifting efficiency.
- Maximum heat dissipation.
- Superior oxidation stability and extended oil change intervals.
- Superior resistance to pre-ignition;
- Low friction.
- Low pour point and extremely high viscosity index, ensuring maximum protection even under significant temperature fluctuations.
- High detergent, anti-corrosion, and anti-rust properties.
- Low sulphur, phosphorus and sulfate ash content.

For further details, please contact the technical department.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio



REDOIL



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

TECHNICAL DATA SHEET

COMPETITION GT4 5W-50

Typical characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	Kg/dm ³	ASTMD7042	0,855
Viscosity 40°C	cSt	ASTMD445	138,5
Viscosity 100°C	cSt	ASTMD445	19,5
Viscosity Index	-	ASTMD2270	161
Flash Point	°C	ASTMD92	228
Freezing point	°C	ASTMD97	-34

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio