



REDOIL



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

TECHNICAL DATA SHEET

COMPETITION GT4 20W-40

Four Stroke Motorcycle Lubricant

SPECIFICS

- API SP/ SN/SM
- JASO T903 JASO MA-MA2
- JASO Quality Category SP

TECHNICAL DESCRIPTION



Extraordinary lubricating fluid 20 winter and medium HTHS (a well-defined design parameter required by the engine manufacturer that is extremely relevant for the evaluation of lubricant suitability). Formulated with GPIII hydroisomerised bases, it has been created through design studies with intervention on the molecule aimed at obtaining a fluid with medium HTHS viscosity values.

Specifically indicated for 4T engines of medium and large displacement road motorbikes equipped with single-cylinder and multi-cylinder engines, it has a special structure that distinguishes it from products of the same category thanks to its ability to ensure greater acceleration with simultaneous reduction of friction. Specifically indicated for all types of 4-stroke engines of road motorbikes with or without oil bath clutches, it can also be used in jet skis, snowmobiles, SXS and ATVs according to the viscosimetric gradations given in the manufacturers' use and maintenance manuals.

The use of such a product ensures:

- Anti-hopping function for improved clutch control;
- Outstanding catalyst protection (low phosphorous and sulphur content JASO MA-2);
- Smooth gear engagement;
- Maximum heat dissipation;
- Excellent oxidation stability and extension of oil changes;
- High pre-ignition counteracting action;
- Low friction;
- Low pour point and very high viscosity index, ensuring maximum protection even with extreme temperature fluctuations;
- High anti-corrosion and anti-rust cleaning properties;
- Low sulphur phosphorus and sulphated ash content.

For further details, please contact the technical department.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio



REDOIL



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

TECHNICAL DATA SHEET

COMPETITION GT4 20W-40

Typical characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	Kg/dm ³	ASTMD7042	0,865
Viscosity 40°C	cSt	ASTMD445	113,2
Viscosity 100°C	cSt	ASTMD445	15,8
Viscosity Index	-	ASTMD2270	149
Flash Point	°C	ASTMD92	233
Freezing point	°C	ASTMD97	-27

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio