



REDOIL

TECHNICAL DATA SHEET



EELQMS

EUROPEAN ENGINE
LUBRICANTS QUALITY

Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

COMPETITION GT4 5W-40

Four Stroke Motorcycle Lubricant

SPECIFICS

- API SP/ SN/SM
- JASO T903 JASO MA-MA2
- JASO Quality Category SP

TECHNICAL DESCRIPTION



Modified synthetic-based lubricant fluid, produced through exclusive production processes aimed at achieving the highest performance. In essence, this technological breakthrough represents the perfect combination of protection of mechanical parts, performance and reduced consumption. Specifically indicated for all types of 4-stroke engines of road motorbikes with or without oil bath clutches, it can also be used in jet skis, snowmobiles, SXS and ATVs according to the viscosimetric gradations given in the manufacturers' use and maintenance manuals.

The use of this product ensures:

- Anti-hopping function for improved clutch control;
- Outstanding catalyst protection (low phosphorous and sulphur content JASO MA-2);
- Smooth gear engagement;
- Maximum heat dissipation;
- Excellent oxidation stability and extension of oil changes;
- High pre-ignition counteracting action;
- Low friction;
- Low pour point and very high viscosity index, ensuring maximum protection even with extreme temperature fluctuations;
- High detergent, anti-corrosion and anti-rust properties;
- Low sulphur phosphorous and sulphate ash content.

For further details, please contact the technical department.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio



REDOIL



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

TECHNICAL DATA SHEET

COMPETITION GT4 5W-40

Typical characteristics

Properties	Unit	Method	Average values
Colour	-	Visual	Amber
Appearance	-	Visual	limpid
Density	Kg/dm ³	ASTMD7042	0,855
Viscosity 40°C	cSt	ASTMD445	95,85
Viscosity 100°C	cSt	ASTMD445	14,8
Viscosity Index	-	ASTMD2270	161
Flash Point	°C	ASTMD92	228
Freezing point	°C	ASTMD97	-37

MODE OF USE

Use in accordance with the recommendations in the user and maintenance manual supplied by the manufacturer. Store in a cool, dry place, protected from direct sunlight and at temperatures not exceeding 60°C (140°F).

SAFETY AND ENVIRONMENT

Use in accordance with the recommendations provided in the Safety Data Sheet. Additional information on MSDS.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio