



REDOIL



EELQMS
EUROPEAN ENGINE
LUBRICANTS QUALITY
MANAGEMENT SYSTEM
Data di prima emissione
19/11/2021

Rev. N°4 del 01/07/2024

TECHNICAL DATA SHEET

GASOLINE ADDITIVE

PETROL FUEL SYSTEM CLEANER ADDITIVE

TECHNICAL DESCRIPTION

This high-detergency additive has been formulated as a decarbonising agent for all gasoline fuel systems.

It is designed to remove deposits caused by residual build-up or decomposition of fuel substances that can accumulate along the entire fuel supply system, such as in injector nozzles, the pump, or the fuel tank.

The main advantages of this unique detergent are the result of its patented formula, which, through regular preventative applications, ensures maximum cleaning efficiency without the necessity for high-cost disassembly operations.

This product guarantees the following benefits:

- Reduced consumption
- Maximum filterability
- Optimal cleaning action
- Decarbonising effect
- Enhanced performance
- Reduced smoke emissions

For further details, please contact the technical department.



P.IVA/C.F.: 03903071219



Via Boscofangone, Zona industriale ASI
80035 – NOLA (NA) – ITALIA
Tel: 081 3151396/97
Fax: 081 3151605
Web: www.siralspa.it
laboratorio@siralspa.it

Responsabile di laboratorio

GASOLINE ADDITIVE

MODE OF USE

It is recommended to use the product at each service interval. To achieve the optimal results, please pour the entire contents of one bottle directly into the gasoline tank. The recommended dosage is 125ml per 20 litres of gasoline.

CHEMICAL AND PHYSICAL CHARACTERISTICS

DENSITY	0,815 g/ml 20°C
APPEARENCE	LIQUID
COLOUR	AMBER
SMELL	AROMATIC
IGNITION TEMPERATURE	>60°C

SAFETY AND ENVIRONMENT

Please, use in accordance with the recommendations provided in the MSDS
Additional information on MSDS.